

Connected Mobility with the Innovative Kymeta™ u8 Terminal

Powered by Intelsat FlexMove



A low-profile, global high-throughput satellite solution for communications-on-the-move.

- Installed on a vehicle or mobile platform and designed to operate at high-speeds
- Ubiquitous, always-on connectivity services
- Up to 10x faster than Mobile Satellite Services (MSS) at a fraction of the cost
- Hybrid connectivity with integrated LTE capability
- Intelsat FlexMove qualified terminal

The Kymeta u8 Ku-band terminal is a complete connectivity solution providing on-the-go communications when and where you need it.

The u8 terminal is designed with Kymeta's signature electronically steered, software-defined technology. This low profile, aerodynamic antenna mounts easily on vehicles to provide a seamless hybrid satellite/cellular connectivity.



Robust design suitable
for a wide range of land
mobility environments



Always-on connectivity
with multi-WAN satellite
and cellular configuration

As the world's first high-throughput satellite (HTS) service for land mobility, **FlexMove** enables global, resilient, on-demand connectivity – even in the most remote and hostile locations.



Powered by the Intelsat Epic
HTS fleet and wide beam
global Ku-band network



Redundant and survivable
network for mission-critical,
data-intensive applications



Kymeta u8 Ku-band satellite terminal:

- Simple power-on startup and auto-acquisition for easy operation
- iDirect iQ 200 and multi-WAN device with global LTE support
- Low power consumption with native DC operation
- Fast tracking, on-the-move connectivity for mobile broadband
- Over-the-air (OTA) software updates
- Complete Ku-band coverage providing maximum reach and performance

SPECIFICATIONS*

ANTENNA TYPE

Kymeta u8 GEO Terminal with integrated LTE capability

DIMENSIONS

W 89.5 cm x D 89.5 cm x H 12.3 cm

TOTAL WEIGHT

25 kg (55 lb.)

Includes modem, hybrid card

FREQUENCIES

TX 13.75 - 14.5 GHz

RX 10.7 - 12.75 GHz

POLARIZATION

Vertical and horizontal, software defined (circular with software upgrade)

EIRP

Up to 46.5 dBW with 20 W BUC

SCAN ANGLES

Az 360°, El +15° to +90°

G/T

Up to 11.5 dB/K

POWER CONSUMPTION (with integrated modem)

~165 W (typical)

<600 W (peak**)

NETWORK INTERFACE

Ethernet, Wi-Fi

RF CABLES

N-type connectors

INPUT POWER

12 - 24 VDC

CERTIFICATIONS IN PROGRESS

CE, UL, RoHS, FCC

OPERATIONAL TEMPERATURE

-40° C to +55° C (ambient)

-40° C to +70° C (with solar load)

AVAILABLE CONFIGURATION

-u8 antenna with integrated antenna control unit and power supply

-iDirect iQ 200 and multi-WAN device with either Global LTE or LTE Band 14 configuration

-RF chain with 20 W low-profile BUC

-Shroud

AVAILABLE ACCESSORIES

-Vehicle mount kit

-Vehicle power kit

-AC-to-DC power kit

-Universal mounting plate for existing u7 mounts

* Specifications as of 1 July 2020. Subject to change.

** Software restriction on peak draw available. May affect antenna performance at low temperature.

©2020 Kymeta Corporation. All Rights Reserved. KYMETA, KYMETA CONNECT, MAKING MOBILE GLOBAL, and CONNECTED BY KYMETA are trademarks of Kymeta Corporation, with registrations or pending applications in the U.S. and/or other countries. All other trademarks are the property of their respective owners.



To learn more about IntelSat FlexMove, visit intelsat.com/land-mobile or contact your local sales representative.

Africa

+27 11-535-4700

sales.africa@intelsat.com

Asia-Pacific

+65 6572-5450

sales.asiapacific@intelsat.com

Europe

+44 20-3036-6700

sales.europe@intelsat.com

Latin America & Caribbean

+1 305-445-5536

sales.lac@intelsat.com

Middle East & North Africa

+971 4-390-1515

sales.mena@intelsat.com

North America

+1 703-559-6800

sales.na@intelsat.com