

# Connected Mobility with the Innovative **HAWK™ u8 Terminal**

Powered by Intelsat FlexMove



## A low-profile, global high-throughput satellite solution for communications-on-the-move.

- Installed on a vehicle or mobile platform and designed to operate at high-speeds
- Ubiquitous, always-on connectivity services
- Up to 10x faster than Mobile Satellite Services (MSS) at a fraction of the cost
- Hybrid connectivity with integrated LTE capability
- Intelsat FlexMove qualified terminal

**The HAWK u8 Ku-band terminal** is a complete connectivity solution providing on-the-go communications when and where you need it.

The HAWK u8 terminal is designed with Kymeta's signature electronically steered, software-defined technology. This low profile, aerodynamic antenna mounts easily on vehicles to provide a seamless hybrid satellite/cellular connectivity.



Robust design suitable  
for a wide range of land  
mobility environments



Always-on connectivity  
with multi-WAN satellite  
and cellular configuration

As the world's first high-throughput satellite (HTS) service for land mobility, **FlexMove** enables global, resilient, on-demand connectivity – even in the most remote and hostile locations.



Powered by the Intelsat Epic  
HTS fleet and wide beam  
global Ku-band network



Redundant and survivable  
network for mission-critical,  
data-intensive applications





## HAWK u8 Ku-band satellite terminal:

- Simple power-on startup and auto-acquisition for easy operation
- iDirect iQ 200 and multi-WAN device with global LTE support
- Low power consumption with native DC operation
- Fast tracking, on-the-move connectivity for mobile broadband
- Over-the-air (OTA) software updates
- Complete Ku-band coverage providing maximum reach and performance

## SPECIFICATIONS\*

### ANTENNA TYPE

HAWK u8 GEO Terminal with integrated LTE capability

### DIMENSIONS

W 89.5 cm × D 89.5 cm × H 14 cm

### TOTAL WEIGHT

34 kg (75 lb.)

Includes modem, hybrid card

### FREQUENCIES

TX 13.75 - 14.5 GHz

RX 10.7 - 12.75 GHz

### POLARIZATION

Vertical and horizontal, software defined (circular with software upgrade)

### EIRP

Up to 46.5 dBW with 20 W BUC

### SCAN ANGLES

Az 360°, El +15° to +90°

### G/T BROADSIDE

9.5 dB/K to 12 dB/K

### POWER CONSUMPTION (WITH INTEGRATED MODEM)

130 W (typical)

250 W (peak)\*\*

### DC INPUT POWER

12 VDC to 36 VDC max

### NETWORK INTERFACE

Ethernet, Wi-Fi

### RF CABLES

N-type connectors

### CERTIFICATIONS IN PROGRESS

CE, UL, RoHS, FCC

### OPERATIONAL TEMPERATURE

-40° C to +55° C (ambient)

-40° C to +70° C (with solar load)

### AVAILABLE CONFIGURATION

u8 antenna with integrated antenna control unit and power supply

iDirect iQ 200 and multi-WAN device with either Global LTE or LTE Band 14 configuration

RF chain with 20 W low-profile BUC

Shroud

### AVAILABLE ACCESSORIES

Vehicle mount kit

Vehicle power kit

AC-to-DC power kit

\* Specifications as of 19 May 2022. Subject to change.

\*\* Software-controlled peak power draw. User-configurable to a higher threshold for very low-temperature operation.

©2023 Kymeta Corporation. KYMETA is a trademark of Kymeta Corporation, with registrations or pending applications for these marks in the U.S. and other countries. All other trademarks are the property of their respective owners.



To learn more about IntelSat FlexMove, visit [intelsat.com/land-mobility](https://intelsat.com/land-mobility) or contact your local sales representative.

### Africa

+27 11-535-4700

[sales.africa@intelsat.com](mailto:sales.africa@intelsat.com)

### Asia-Pacific

+65 6572-5450

[sales.asiapacific@intelsat.com](mailto:sales.asiapacific@intelsat.com)

### Europe

+44 20-3036-6700

[sales.europe@intelsat.com](mailto:sales.europe@intelsat.com)

### Latin America & Caribbean

+1 305-445-5536

[sales.lac@intelsat.com](mailto:sales.lac@intelsat.com)

### Middle East & North Africa

+971 4-390-1515

[sales.mena@intelsat.com](mailto:sales.mena@intelsat.com)

### North America

+1 703-559-6800

[sales.na@intelsat.com](mailto:sales.na@intelsat.com)