

The Fully Automated, Flat Panel Starwin uSat FL60P Terminal

Powered by Intelsat FlexMove



A portable, cost-effective comms-on-the-pause satellite terminal.

- Ubiquitous, always-on portable connectivity
- Up to 20x faster than Mobile Satellite Services (MSS) at a fraction of the cost
- Suitable for enterprise, emergency response, public safety organizations, NGOs and more
- Intelsat FlexMove qualified terminal

The game-changing Starwin uSat terminal uses an advanced, high-gain flat array antenna system. With automatic pointing and easy-to-deploy set up, end-users can quickly acquire connectivity with the Intelsat FlexMove network in just minutes.

The uSat terminal meets the demand of mission-critical, on-the-go operations by making satellite communications simple and easy. A wide range of applications may be seamlessly enabled through the FlexMove fully provisioned managed service.



Powerful, highly compact
terminal designed for temporary
use in a fixed location



Reliable data, voice, and
video transfer in areas
without terrestrial networks

As the world's first high throughput satellite (HTS) service for land mobility, **FlexMove** enables global, resilient, on-demand connectivity – even in the most remote and hostile locations.



Powered by the Intelsat Epic
HTS fleet and wide beam
global Ku-band network



Redundant and survivable
solution for mission-critical,
data-intense applications



INTELSAT

StarWin





The Starwin uSat Flat Panel Portable Auto-Pointing Terminal

- All-in-one, fully integrated with modem, BUC, LNB, Wi-Fi and power supply
- Automatically points and connects to satellites almost anywhere in the world
- 3" OLED display facilitates locking in satellite beam and checking working status
- Compact in size with optional backpack for easy transport
- Pre-configured network options file allows for secure satellite lock within minutes
- Able to operate by both AC and DC power via integrated rechargeable battery

SPECIFICATIONS

MODEL NO

FL60P-E

ANTENNA TYPE

Slotted waveguide array antenna

EQUIVALENT TO PARABOLIC ANTENNA SIZE

0.6m

FREQUENCY RANGE:

Tx: 13.75~14.50GHz

Rx: 10.95~12.75GHz

POLARIZATION

Dual Linear

RECEIVING GAIN

≥35dBi

TRANSMITTING GAIN

≥36dBi

G/T

13dB/K

FIRST SIDELobe

≥15dB

SATELLITE ACQUISITION

Automatically pointing to satellite,
level error<0.2dB

AZIMUTH RANGE

Unlimited, fine tune ±70°

ELEVATION RANGE

7° ~ 90°

POLARIZATION

±88°

POWER SUPPLY

AC 90~264V (DC 24V ±5% Optional
Power Supply).

Integrated rechargeable high-capacity
battery pack (installed in base of
terminal). Supports up to 3 hours of use.

MAX POWER CONSUMPTION

120W (with 6W BUC, searching process)
85W (Access Network)

TERMINAL DIMENSIONS

(not including cables and backpack)

(L×W×H): 680×650×240 mm

TOTAL TERMINAL WEIGHT

(not including cables and backpack)

18 Kg (Max)

WIND (Operational)

14m/s (50km/h)

OPERATIONAL TEMPERATURE

-25°C to +50°C

INGRESS PROTECTION

IP-66

HUMIDITY

0 ~ 95%

SATELLITE MODEM

iDirect IQ 200 modem

TYPICAL BUC

6W

TYPICAL LNB

PLL LNB 30K for TDMA systems

PLL LNB 5K for SCPC systems

WIRELESS ROUTER SUPPORTED PROTOCOLS

IEEE 802.11b/g/n at 2.4GHz

LAN PORT (RJ45)

Gigabit Ethernet

BLUETOOTH DEVICE

v4.2

GNSS DEVICE SUPPORTS

GPS/GLONASS/BeiDou-2/Galileo

CERTIFICATIONS

FCC, CE, ANATEL



Africa

+27 11-535-4700

sales.africa@intelsat.com

Asia-Pacific

+65 6572-5450

sales.asiapacific@intelsat.com

Europe

+44 20-3036-6700

sales.europe@intelsat.com

Latin America & Caribbean

+1 305-445-5536

sales.lac@intelsat.com

Middle East & North Africa

+971 4-390-1515

sales.mena@intelsat.com

North America

+1 703-559-6800

sales.na@intelsat.com