



FlexMove LEO

Low-Earth orbit high-speed, low-latency satellite connectivity for live broadcasting



Low-Earth Orbit (LEO) Connectivity Solution for broadcasting news, events, and sports

As part of IntelSat's FlexMove portfolio of services, and through our partnership with Eutelsat OneWeb, IntelSat offers FlexMove LEO for broadcast applications requiring the high-speed and low-latency connectivity of a low-Earth orbit network.

With a FlexMove LEO managed service, broadcasters and media organizations gain the added benefit of low-Earth orbit broadcast-grade connectivity ensuring reliable, real-time video distribution and contribution whenever and wherever needed.

The Best of Both Worlds

In one place (GEO and LEO)



Advantages of OneWeb LEO Network Service from IntelSat



Service

IntelSat managed LEO service with 24x7/365 personal support



High Speed

Up to 150 Mbps download and 30 Mbps upload



Low Latency

~70 milliseconds for faster response times of applications



Flexible

Integrated with IntelSat's Managed Media Services portfolio



Business Centered

Designed for full-time and occasional use applications on the move

Advanced Low-Earth Orbit Ku-band Satellite Terminals

Cutting-edge technology. Robust connectivity. Easy deployment.

Intellian OW10HL Compact Terminal

Intellian's compact flat panel is ideal for a variety of communications-on-the-pause (COTP) applications.

- **Dimensions:** 56 cm x 45 cm x 12 cm / 22 in. x 17.8 in. x 4.7 in. plus CNX-WiFi 21 cm x 17 cm x 8 cm / 8.2 in. x 6.7 in. x 3.1 in.
- **Weight:** Terminal 12.2 kg / 26.9 lb. plus adjustable mount adapter 1.5 kg / 3 lb. plus CNX-WiFi 0.6 kg / 1.3 lb.
- **Operating Temperature:** -40° to +55°C / -40° to 131°F for terminals, CNX units at 0° to 40°C / 32-104°F
- **Ingress Protection:** Terminals are IP66. CNX units are not weatherized. CNX-WiFi is IP44 rated.



Kymeta u8 Hawk LEO

Kymeta's electronically scanning terminal designed to provide reliable connectivity with moving satellites. Full duplex, single aperture, Ku-band flat-panel antenna, electronically steered holographic beam-forming array.

- **Dimensions:** 89.5 cm x 89.5 cm x 14 cm / 35.2 in. x 35.2 in. x 5.5 in.
- **Weight:** 30.1 kg / 66 lb.
- **Operating Temperature:** -40 °C to +55 °C
- **Ingress Protection:** IP66



Powered by a Broadcast-grade Satellite Network Service

As the foundational architects of satellite technology, designing global network solutions that fit specific user needs is in our DNA.

Learn more about how we can help with your connectivity needs at:

[Intelsat.com/flexmove](https://www.intelsat.com/flexmove)

About Intelsat

Intelsat's global team of professionals is focused on providing seamless and secure, satellite-based communications to government, NGO and commercial customers through the company's next-generation global network and managed services. Bridging the digital divide by operating one of the world's largest and most advanced satellite fleet and connectivity infrastructures, Intelsat enables people and their tools to speak over oceans, see across continents and listen through the skies to communicate, cooperate and coexist. Since its founding six decades ago, the company has been synonymous with satellite-industry "firsts" in service to its customers and the planet. Leaning on a legacy of innovation and focusing on addressing a new generation of challenges, Intelsat team members now have our sights on the "next firsts" in space as we disrupt the field and lead in the digital transformation of the industry.

Contact Sales

Africa

+27 11-535-4700
sales.africa@intelsat.com

Asia-Pacific

+65 6572-5450
sales.asiapacific@intelsat.com

Europe

+44 20-3036-6700
sales.europe@intelsat.com

Latin America & Caribbean

+1 305-445-5536
sales.lac@intelsat.com

Middle East & North Africa

+971 4-390-1515
sales.mena@intelsat.com

North America

+1 703-559-6800
sales.na@intelsat.com

